

# Essentium Copolyester PA-CF SAFETY DATA SHEET

# **ESSENTIUM PA-CF**

Thank you for your interest in Essentium's products. We are providing this safety data sheet [SDS] as a courtesy to your request. We certainly expect you to read the entire SDS and to call us with any required points of clarification. Please follow all precautions identified in this document.

Copyright, May 2019, Essentium Inc., all rights reserved. Copying and/or disseminating this information for the purpose of properly utilizing Essentium's products is allowed provided that: (1) no changes are made to the document and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit. This product is not regulated under, and a SDS is not required for this product by the OSHA Hazard Communication Standard (29 CFR 1910.1200) because, when used as recommended or under ordinary conditions, it should not present a health and safety hazard. However, use or processing of the product not in accordance with the product's recommendations or not under ordinary conditions may affect the performance of the product and may present potential health and safety hazards.

# **SECTION 1: PRODUCT AND COMPANY IDENTIFICATION**

Product Name:	Essentium PA-CF		
Supplier:	Essentium Inc.		
Address:	19025 N. Heatherwilde Blvd. Suite 100 Pflugerville, TX 78660		
Manufacturer:	Essentium Inc.		
Address:	19025 N. Heatherwilde Blvd. Suite 100 Pflugerville, TX 78660		
Supplier Emergency Contacts & Phone:	Essentium Inc. Email: Sales@Essentium3D.com Website: Essentium3D.com		
Revision Date	05/27/2019		

Essentium.com

ESSENTIUM

#### **SECTION 2: COMPOSITION/INFORMATION ON INGREDIENTS**

INGREDIENT	CAS NO.	<b>WT</b> %
2,4,8,10-Tetraoxa-3,9-diphosphaspiro[5.5]undecane, 3,9-bis[2,4- bis(1,1-dimethylethyl)phenoxy]->=0.3 -	26741-53-7	< 1.0%
Polyamide copolymer	N/A	> 89%
Chopped carbon fiber	N/A	10%

All ingredients in quantities > 1.0% (0.1% for carcinogens) that are potentially hazardous per OSHA definitions.

#### **SECTION 3: HAZARDS IDENTIFICATION**

According to Regulation 2012 OSHA Hazard Communication Standard; 29 CFR Part 1910.1200. Classification of the product: No need for classification according to GHS criteria for this product Label elements: No need for a hazard warning label according to GHS criteria for this product Other hazards: No specific dangers known if the regulations/notes for handling and storage are considered

#### **SECTION 4: FIRST AID MEASURES**

The following first aid recommendations are based on an assumption that appropriate personal and industrial best practices are followed. Precautions should be taken to avoid inhalation and eye contact.

General Advice: Remove contaminated clothing. Burns caused by molten material may require hospital treatment.

Eye contact: Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Call a physician immediately.

**Skin contact:** Adverse effects are not expected from accidental skin contact following occupational exposure. After contact with skin, wash with soap and water. If skin irritation persists, call a physician. Cool skin rapidly with cold water after contact with hot polymer. DO NOT attempt to remove hot polymer from skin or contaminated clothing as skin may be easily damaged. Call a physician immediately.

**Ingestion:** Drink water as a precaution. Never give anything by mouth to an unconscious person. Do not induce vomiting without medical advice. Call a physician immediately.

Inhalation: Move to fresh air, keep person calm. Call a physician immediately.

#### **SECTION 5: FIRE-FIGHTING MEASURES**

Suitable extinguishing media: Carbon dioxide, water spray, dry powder, and foam

Unsuitable extinguishing media: None known

**Special protective equipment for firefighters:** As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear

Essentium.com



**Special hazards arising from substance:** Hazards during fire-fighting: carbon monoxide, carbon dioxide, and polycyclic aromatic hydrocarbons can be emitted at > 250 °C. Under special fire conditions traces of other toxic substances are possible. Formation of further decomposition and oxidation products depends upon the fire conditions.

Further information: Dispose of fire debris and contaminated extinguishing water in accordance with official regulations

#### **SECTION 6: ACCIDENTAL RELEASE MEASURES**

Risk: High risk of slipping due to spillage of product

Personal precautions: No special precautions necessary

Environmental precautions: No special precautions necessary

Methods for cleaning up: Spills should be contained and placed in suitable containers for disposal

# **SECTION 7: HANDLING AND STORAGE**

**Safe handling advice:** Use personal protective equipment. Avoid contact with skin and eyes. Low hazard for usual industrial or commercial handling. Workers should be protected from the possibility of contact with molten material during fabrication. Avoid dust formation. If small particles are generated during further processing, handling, or by other means, combustible dust concentrations in air may form. Protect from moisture and impurities. Keep the floor clear. Provide suitable exhaust for ventilation during the drying process and in the area surrounding the melt outlet and processing machines.

Storage stability: Protect against moisture

Suitable materials for containers: LDPE, aluminum, HDPE, carbon steel (iron)

Precautions: No special precautions required

Dangerous reaction: No dangerous reactions are known

### **SECTION 8: EXPOSURE CONTROLS / PERSONAL PROTECTION**

Exposure control: No occupational exposure limits known

Advice on system design: Provide local exhaust ventilation to control dusts/vapors

#### Personal protective equipment:

Eye protection: Safety goggles with side-shields to protect from hot molten substance/product

Skin and body protection: Body protection must be chosen based on level of activity and exposure

**Respiratory protection:** Wear respiratory protection if ventilation is inadequate. Wear a NIOSH certified (or equivalent) particulate respirator. Wear a NIOSH certified (or equivalent) organic vapor/particulate respirator.

Hand protection: Preventive skin protection, gloves

**Hygiene measures:** Wear protective clothing to prevent contact during mechanical processing and or hot melt conditions. Avoid inhalation of dust. When using, do not eat, drink, or smoke. Hands and/or face should be washed before breaks and at the end of the shift. At the end of the shift the skin should be cleaned, and skin care agents applied.

Special hazard: Workers should be protected from the possibility of contact with molten material during fabrication

Essentium.com



# **SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES**

Physical State:	Solid filament	Vapor Pressure:	Not applicable
Color:	Black	Density:	1.10 - 1.60 g/cm <sup>3</sup> (20 °C)
Odor:	Faint odor	Relative Density:	No data available
Odor Threshold:	Not applicable	Bulk Density:	500 - 800 kg/m <sup>3</sup>
pH:	Not applicable	Vapor Density:	Not applicable
Boiling Point / Boiling Range:	Not available	Partitioning coefficient	Not applicable
Melting Point / Melting Range:	Approx. 190°C	n-octanol/water (log Pow):	
Sublimation Point:	Not applicable	Self-Ignition Temperature:	Not self-igniting
Flash Point:	> 400°C	Thermal Decomposition:	> 320°C
Flammability:	Not self-igniting	Water Solubility:	Insoluble
Flammability of Aerosol:	Not applicable	Evaporation rate:	Not applicable
Products:	Form flammable aerosols	Viscosity, dynamic:	Not applicable
Lower Explosion Limit:	For solids not relevant for clas-	Viscosity, kinematic: Solubility (quantitative):	Not applicable
	sification and labeling		No applicable information available
Upper Explosion Limit:	For solids not relevant for clas- sification and labeling	Solubility (qualitative):	No applicable information
Autoignition temperature:	Not applicable		available

# **SECTION 10: STABILITY AND REACTIVITY**

**Reactivity:** None expected under conditions of normal use

Chemical stability: Stable under recommended storage conditions

Possibility of hazardous reactions: No hazardous reactions known

Conditions to avoid: > 320°C

Hazardous decomposition products: Carbon monoxide, carbon dioxide, hydrogen cyanide, caprolactam, ammonium hydroxide, nitriles

### **SECTION 11: TOXICOLOGICAL INFORMATION**

Inhalation: Not inhalable due to the properties of the product

Irritation: Thermal decomposition of the product can irritate eyes, skin, and respiratory tract

Essentium.com



**Eyes:** Molten material will cause thermal burns

Skin: Molten material will cause thermal burns

Other: No specific target organ toxicity (STOT) No sensitizing effect No aspiration hazard No known chronic effects Chemical structure does not suggest a specific alert to genetic toxicity Chemical structure does not suggest a specific alert to carcinogenicity Chemical structure does not suggest a specific alert to reproductive toxicity Chemical structure does not suggest a specific alert to reproductive toxicity Chemical structure does not suggest a specific alert to reproductive toxicity

# **SECTION 12: ECOLOGICAL INFORMATION**

Aquatic toxicity: There is a high probability that the product is not acutely harmful to aquatic organisms

Biodegradable: Inert and non-degradable

# **SECTION 13: DISPOSAL CONSIDERATIONS**

**Waste from residues / unused products:** In accordance with local, state, and national regulations - should not be released into the environment. Do not contaminate ponds, waterways or ditches with chemical or used container. Incinerate or dispose in a licensed facility.

Contaminated packaging: Dispose of in accordance with national, state, and local regulations

THE COMPANY HAS NO CONTROL OVER THE MANAGEMENT PRACTICES OR MANUFACTURING PROCESSES OF PARTIES HANDLING OR USING THIS MATERIAL. THE INFORMATION PRESENTED HERE PERTAINS ONLY TO THE PRODUCT AS SHIPPED IN ITS INTENDED CONDITION.

# **SECTION 14: TRANSPORT INFORMATION**

U.S. DEPARTMENT OF TRANSPORTATION | PROPER SHIPPING NAME: WATER TRANSPORTATION | PROPER SHIPPING NAME: AIR TRANSPORTATION | PROPER SHIPPING NAME: Not regulated for transportation Not regulated for transportation Not regulated for transportation

# **SECTION 15: REGULATORY INFORMATION**

Regulatory requirements are subject to change and may differ between locations. It is the User's responsibility to ensure that all activities comply with all federal, state or provincial and local laws and regulations. The following specific information is made for the purpose of complying with numerous national, federal, state or provincial, and local laws and regulations. See other sections for health and safety information.

### **U.S. REGULATIONS**

Sara 313 title III:Not listedTSCA Inventory List:Listed



EPCRA 311/312:	Not hazardous		
NFPA Hazard Codes:	Health: 1	Fire: 1	Reactivity: 0
HMIS III Rating:	Health: 1	Flammability: 1	Physical hazard: 0
INTERNATIONAL REGULATIONS:	Contact Essentium Inc. for more information.		

Not meant to be all inclusive - selective regulations represented.

# **SECTION 16: OTHER INFORMATION**

# DISCLAIMER:

Essentium Inc. nor any of its subsidiaries assumes any liability whatsoever for transporting/handling the product. It is the buyer's/user's/ licensee's responsibility to ensure that its activities comply with all federal, state, provincial, or local laws and import/export requirements. We assume no responsibility regarding the suitability of this information for the user's intended purposes or for the consequences of its use. Essentium Inc. makes no warranties, expressed or implied, including but not limited to, any implied warranty of merchantability or fitness for a particular purpose or course of performance or usage of trade. Final determination of suitability of any material is the sole responsibility of the user.

